



CARBAND Fitting Guidelines

Your Carband is a large continuous fully breathable resilient piece of technically developed material made from a polyester and Lycra spacer weave. Built in a 3-D Construction for maximum stretch giving a secure tight fit. Your Carband must be treated with these characteristics in mind. Please take extra care when first fitting The Carband. Carband is unique, you will probably have not fitted anything like it before, so take your time, it's NOT a race against the clock, after all it's designed for medium to long term parking. It should take between 1 - 2 minutes with two persons and 3 - 5 minutes individually.

It is suggested that two persons fit the Carband, although after practice an individual can fit the Carband with ease and patience. The Carband is designed to fit tightly, DO NOT FORCE IT, if you feel it is over stretching, we will happily replace the Carband for the correct size if it's too tight or too slack. It is important at the point of ordering you state the Make, Model & type of your vehicle (Saloon, Estate, Hatch Back etc). The current sizes range from Small, Medium, Large & Extra Large, we can also make bespoke sizes for any other vehicles, sizes to order only.

Although Carband is designed to hug and form on most ridges and angles, sharp protruding objects must be removed, such as towing eyes, sharp edged license plate holders and any other sharp protrusions. Carband will wrap over front lip spoilers and all vents and COOLED non sharp exhaust pipes. Most exhausts have rolled steel edge, carbon or plastic edges and we recommend checking this before use?

Common sense must prevail when fitting Carband, sharp or razor like edges must be avoided, as well as hot exhaust pipes or other vents, including hot calipers and brakes.

FITTING

Ensure the vehicle is clean, particularly when using the Carband without a cover. Remember why you are using your Carband to protect your vehicle, you would not want to fit any cover over an unclean vehicle.

If fitting with a car cover, ensure the cover is properly secured and square on the vehicle, although you will adjust after fitting, pulling the car cover tight first. Once the Carband is fitted, adjust the cover to the vehicle under the Carband again.

Two Person Fit

Both take the Carband tightly held at either end and stretch it out like a large sheet. One person walk to the back of the vehicle, and again like a fitted sheet place the Carband over each corner while the other person keeps some tension on the Carband. Keep the tension, not allowing the Carband to drop on the ground or behind the back wheels. Maintain the tension walk to the front (opposite side to your partner) of the vehicle, carefully avoiding wing mirrors and external aerals. Feed the Carband through your arms and hands while moving to the front of the vehicle. You will both feel the tension of the Carband increasing. Now you are both at the front of the vehicle and probably in line with the front wheels. While one person holds the Carband firmly, gripping the bottom of the Carband with their hand and forearm taking the tension, the other similarly then proceeds to take the full stretch and secure round the front of the vehicle, the second person then does the same, releasing the Carband into position while gently sliding your forearm away.

Your Carband is now fitted and all that remains is the tweaking to cover and line up the Carband to give maximum coverage.

One Person Fit

This process can be used with a single person fitting Carband, but instead of using a partner, you will be using the integrity of the vehicle, important to keep good constant tension, with the Carband firmly in place on the vehicle corners. It is important to follow these instructions, grabbing a handful and just pulling without taking the strain without an extra hand or forearm is not recommended. You will find after fitting your Carband you will spend more time tweaking for the perfect fit and look!

You can find a fitting video here;

<http://www.youtube.com/watch?v=c0urXOhyWc>

CARE

Your Carband can be cleaned with low temperature water and left to dry thoroughly. It is a fully breathable fabric and should be stored in a breathable atmosphere. Please avoid any sharp objects coming into contact.

Although the material has a high resistance to heat it is not advised to place it over hot exhausts or vehicle externals. If the Carband is not in use, roll it up neatly and store as advised.

If you have any queries please contact your supplier who will be pleased to help